HNP Mikrosysteme GmbH



Due to careful material selection and advanced microtechnology design as well as high manufacturing precision micro annular gear pumps open a new dimension in pump technology. Four series of rotary positive displacement pumps allow precise and nearly pulsation-free dispensing of smallest quantities of liquids. The dosage volumes cover the sub-micro litre to litre range for both nonlubricating and highly viscous liquids. HNP Mikrosysteme offers also comprehensive micro-dosing systems. The most significant characteristics of the pumps are their small dimensions, high operating lives as well as high dosage precision even for the smallest amounts of non-lubricating liquids. Thanks to DC drives and comfortable control the pumps offer high functionality and are easy to operate. The High Performance as well as the Hermetic and Chemically Inert mzr[®] Pump Series are employed in application fields such as chemical process technology, assembly as well as dosage and filling techniques. The Low Pressure Pump Series corresponds to the requirements of instrumental analytics, fuel cells and OEM applications as far as dosage of low viscosity liquids is concerned. The Modular Series allows customized material selection for each component of the pump depending on chemical compatibility with the manipulated liquid.



- High dosage precision precision CV < 1 % at low volumes
- Min. dosage volume 0,25 µl
- Low flow rates
 1,5 µl/min...1152 ml/min
- Compact dimensions
- High differential pressures
 achievable even for low viscosity liquids
- Long service life wear-resistant tungsten carbide and ceramics
- Broad viscosity range
 0,3 1.000.000 mPas
 solvents, water, adhesives, paints, grease, gel
- Pulseless delivery, low shear stress
 rotary micro annular gear technology

















Range of products

			V _g [µl] 0.	flow ra	ite [ml/min] 1 10 100	1000	min. dosage volume [µl]	diff 0 5	pressi	ure [bar] 100	viscosit	ty [mPas] 100 104
	Low pressure series	mzr-2521	1.5	0.0015* 0.1	5 9		0.25	1.5			0.3 100	1000*
41	– compact dimensions – low pressure range – tungsten carbide Ni-based, stainless steel 316L	mzr-2921	3	0.003* 0.3	18		0.5	3			0.3 100	1000*
Provide State	seals: PTFE, FPM, optional: EPDM, FFPM – low viscosity liquids – DC-motor with graphite brushes	mzr-4622	12	0.012*	1.2 72		2	5			0.3 100	1000*
		mzr-7223	48	0.048*	4.8 288		30	5	8*	_	0.3 100	1000*
н	ligh performance series	mzr-2905	3	0.003	18		0.5		30		0.3	50,000
-P	 tungsten carbide Ni-based, stainless steel 316L seals: PTFE, FPM, optional: EPDM, FFPM 	mzr-4605	12	0.012	72		2		50		0.3	50,000
~	 differential pressure range 40 bar (max 150 bar) low and high viscosity liquids 	mzr-7205	48	0.048	288		30		40		0.3	1,000,000
	 DC-servomotor with integrated controller modular system: fluidic seal module, 	mzr-7208	48	0.048	288		30			150	0.3	1,000,00
	heat insulation module, electrical heating, double shell heating and cooling module, reduction gear, high-power motors	mzr-11508	192	0.1	92 11	152	100			150	0.3	150,000
		mzr-11507	192		29 11	152	100			150	0.3	150,000
	Ex-Pumps	mzr-2909 Ex	3	0.003	14		0,5	5			0.3	5000
Le	 for pump heads of high performance series and the hermetic inert series Ex-certification ATEX, EU directive 94/9/EEC 	mzr-4609 Ex	12	0.012	56		2		10		0.3	5000
	 CE Ex II 2 G c T4 X, CE Ex II 2 G c T5 X tungsten carbide Ni-based, stainless steel 316L 	mzr-7209 Ex	48	0.048	225		30		40		0.3 5	5000
	or ceramics, alloy C22 seals: PTFE, FPM, optional: EPDM, FFPM	mzr-11507 Ex	192		29* <mark>58</mark> 11	152	100		8	0	0.3	5000
		mzr-6359 Ex	24	0.024	112		15		15		0.3 100	
		mzr-7259 Ex	48	0.048	225		30		20		0.3 100	
	Modular pump series	mzr-2542	1.5	0.0015* 0.1	5 9		0.25	1.5			0.3 100	1000*
	 chemically inert, compact dimensions configurable materials: ceramics, opt. tungsten carbide; alloy C276/C22, optional PEEK™; 	mzr-2942	3	0.003* 0.3	18		0.5	3			0.3 100	1000*
13	seals: PTFE, FPM, optional: EPDM, FFPM. – DC-motor with graphite brushes	mzr-7245	48	0.048	288		30	5	40*		0.3 1	0,000
He	ermetic inert pump series											
a >	 chemically inert materials industrial equipment Al₂O₃, ZrO₂ ceramics, alloy C22, SSiC, Kalrez[®] 	mzr-6355	24	0.024	288		30		15 20		0.3 10	
	 hermetic magnetic coupling DC-servomotor with integrated controller 											
			V/ -	Lucolocomont vol	1000		× with acco	COLOC	o a biz	an recolution	oncodor (to vod reor

Applications fields



- Robotic sample processor
- Analytical instrumentation
- Sampling
- Micro reaction technology
- Fuel cells
- Minimum quantity lubricating systems
- Aromatizing, flavoring
- Particle analysis
- Buoy water analysis
- PCB cooling
- Ink-jet printing technology
- Biological cell handling
- DNA analysis
- Medicine filling

HNP Mikrosysteme GmbH

Juri-Gagarin-Ring 4 D-19370 Parchim Telefone +49 3871|451-301 +49 3871 451-333 Fax E-mail info@hnp-mikrosysteme.de www.hnp-mikrosysteme.de



- Automated application of silicone sealant beads
- Color marking applicationSpray-coating of blood test tubes
- Mini plant technology
- Polymer development
- PU filling
- Application of separating agents in the plastic deformation process
- Technically challenging dosage from or into vacuum
- Dispensing of polishing slurry in the wafer manufacturing process
- Tin plate lubrication
- Micro hydraulics



Ink cartridge filling

12

- Milling head control mechanism for sewer channel robots
- Silicone application on medical disposables
- Nozzle testing in heating engineering
- Dosing of additives into extruder
- On-line color mixing system for paints
- Dispensing of printing inks
- Dosage of UV-curing adhesives
- Lubricant dosage in the watch/clock assembly
- Micro hydraulic aggregate for helicopters
- Filling of radioactive isotope solutions
- Dosage of liquid metals (mercury, sodium)
- Polyurethane filling

Contact details for different application fields

Process Engineering and International Sales Jana Hertel, Phone +49 3871|451-305 Chemical Engineering and Process Engineering Carsten Damerau, Phone +49 3871|451-347 Philipp Adryan, Phone +49 3871|451-351 Biotechnology and Analytical Instrumentation Dorothee M. Runge, Phone +49 3871|451-318 Mechanical Engineering, Engineering Industry Frank Kunze, Phone +49 3871|451-310 Fuel Cell and Automotive Thomas Kregelin, Phone +49 3871|451-303